

Features

- ▶ LED Backlight Unit
- ▶ HD-SDI Resolution
- ▶ 3D Comb Filter / De-interlacing
- ▶ Connectivity – RGB , S-Video , 2x BNC In & Out, 2 x HDMI , HD-SDI In & Out , Audio
- ▶ Built-In Stereo Speakers
- ▶ Multi Language OSD Support
- ▶ Metal Cabinet with Rear Pedestal / VESA Mount



HD-SDI



	Model	ICC156NPS	ICC185NPS	ICC215NPS	ICC230NPS
Display	Screen Size(Inch/BLU)	15.6 , LED	18.5 , LED	21.5 , LED	23.0 , LED
	Resolution	1366 x 768	1366 x 768	1920 x 1080	1920 x 1080
	Active Area (mm)	344.232 x193.536	409.8 x 230.4	476.64 x 268.11	509.184 x 286.416
	Pixel Pitch (mm)	0.27675 x 0.27675	0.30 x 0.30	0.24825 x 0.24825	0.265 x 0.265 mm
	Brightness (cd/m ²)	350	250	250	250
	Contrast Ratio	500 : 1	1,000 : 1	3,000 : 1	1,000 : 1
	Aspect Ratio	16 : 9	16 : 9	16:9	16:9
	Display Color	16.7M	16.7M	16.7M	16.7M
	Response Time (ms)	8	5	25	5
	Viewing Angle (degree)	170 / 160	170 / 160	178 / 178	170 / 160
Interface	Lamp Life Time (Hours)	50,000	30,000	30,000	30,000
	VGA In / Trigger In	1 / 1	1 / 1	1 / 1	1 / 1
	DVI In / HDMI In	1 / 2	1 / 2	1 / 2	1 / 2
	S-Video In / Component In	1 / 1	1 / 1	1 / 1	1 / 1
	BNC In / Out	2 / 2	2 / 2	2 / 2	2 / 2
	HD-SDI In / Out	1 / 1	1 / 1	1 / 1	1 / 1
	PC Stereo In / RCA	1 / 1	1 / 1	1 / 1	1 / 1
Audio	Built in Speakers	2W x 2 , Stereo	2W x 2 , Stereo	2W x 2 , Stereo	2W x 2 , Stereo
Special Features	Filter Type	3D Comb-filter	3D Comb-filter	3D Comb-filter	3D Comb-filter
	De-interlacing / PIP	Yes	Yes	Yes	Yes
	Noise Reduction Control	Yes	Yes	Yes	Yes
	Auto Source Sequencing	Yes	Yes	Yes	Yes
	Protection Glass	Optional	Optional	Optional	Optional
	Remote Controller	Optional	Optional	Optional	Optional
Cabinet	Multi Lingual Language	English, Spanish, French, German, Italian			
	Material /Stand Type	Metal / Rear Pedestal	Metal / Desk Top	Metal / Desk Top	Metal / Desk Top
Power	Consumption : < On	<15W	<20W	<25W	<30W
	Electrical Ratings	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)
Circum-stance	Operating Temperature	0 ~ 50°C	0 ~ 50°C	0 ~ 50°C	0 ~ 50°C
	Storage Temperature	-20 ~ 60°C	-20 ~ 60°C	-20 ~ 60°C	-20 ~ 60°C
Mounts	VESA Mounts Size (mm)	100 x 100	100 x 100	100 x 100	100 x 100

Features

SECURITY CCTV PREMIUM PROGRESSIVE LEVEL



HD-SDI



ICC240NP



ICC27/32/42NP

- ▶ LED Backlight Unit
- ▶ HD-SDI Resolution
- ▶ 3D Comb Filter / De-interlacing
- ▶ Connectivity – RGB , S-Video , 2x BNC In & Out, 2 x HDMI , HD-SDI In & Out , Audio
- ▶ Built-In Stereo Speakers
- ▶ Multi Language OSD Support
- ▶ Metal Cabinet with Rear Pedestal / VESA Mount

Model		ICC240NPS	ICC270NPS	ICC320NPS	ICC420NPS
Display	Screen Size(Inch/BLU)	24 , LED	27 , LED	32 , LED	42.0 , LED
	Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
	Active Area (mm)	531.36 x 298.89	597.6 x 336.15	698.4 x 392.85	930.24 x 523.26
	Pixel Pitch (mm)	0.27675 x 0.27675	0.31125 x 0.31125	0.3637 x 0.3637	0.4845 x 0.4845 mm
	Brightness (cd/m ²)	250	300	350	350
	Contrast Ratio	1,000 : 1	3,000 : 1	5,000 : 1	3,000 : 1
	Aspect Ratio	16 : 9	16 : 9	16:9	16:9
	Display Color	16.7M	16.7M	16.7M	16.7M
	Response Time (ms)	5	12	8	6.5
	Viewing Angle (degree)	170 / 160	178 / 178	178 / 178	178 / 178
	Lamp Life Time (Hours)	30,000	30,000	30,000	30,000
Interface	VGA In / Trigger In	1 / 1	1 / 1	1 / 1	1 / 1
	DVI In / HDMI In	1 / 2	1 / 2	1 / 2	1 / 2
	S-Video In / Component In	1 / 1	1 / 1	1 / 1	1 / 1
	BNC In / Out	2 / 2	2 / 2	2 / 2	2 / 2
	HD-SDI In / Out	1 / 1	1 / 1	1 / 1	1 / 1
	PC Stereo In / RCA	1 / 1	1 / 1	1 / 1	1 / 1
Audio	Built in Speakers	2W x 2 , Stereo	7W x 2 , Stereo	7W x 2 , Stereo	7W x 2 , Stereo
Special Features	Filter Type	3D Comb-filter	3D Comb-filter	3D Comb-filter	3D Comb-filter
	De-interlacing / PIP	Yes	Yes	Yes	Yes
	Noise Reduction Control	Yes	Yes	Yes	Yes
	Auto Source Sequencing	Yes	Yes	Yes	Yes
	Protection Glass	Optional	Optional	Optional	Optional
	Remote Controller	Optional	Optional	Optional	Optional
Cabinet	Multi Lingual Language	English, Spanish, French, German, Italian			
	Material /Stand Type	Metal / Rear Pedestal	Metal / Desk Top	Metal / Desk Top	Metal / Desk Top
Power	Consumption : < On	<35W	<45W	<55W	<65W
	Electrical Ratings	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)
Circum-stance	Operating Temperature	0 ~ 50°C	0 ~ 50°C	0 ~ 50°C	0 ~ 50°C
	Storage Temperature	-20 ~ 60°C	-20 ~ 60°C	-20 ~ 60°C	-20 ~ 60°C
Mounts	VESA Mounts Size (mm)	100 x 100	200 x 200	200 x 200	200 x 200